DECLARATION OF PERFORMANCE

DOP.03013

Version: 2.0/EN

Revision Date: May / 2021



Printing date: May 18, 2021

1. UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:

REABILITA RR 20

2. INTENDED USES:

Industrial mortar of inorganic binders for internal and external rendering of walls and ceilings.

3. MANUFACTURER:

Secil Martingança, S.A. Apartado 2 EC Maceira 2406-909 Maceira LRA **Trade Name:** SECILTEK

4. SYSTEM OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PRODUCT PERFORMANCE:

System 4

5. HARMONISED STANDARD:

EN 998-1:2016

SECILTEK carried out the determination of the product-type on the basis of type testing, type calculations, tabulated values and factory production control.



DECLARATION OF PERFORMANCE

DOP.03013

Version: 2.0/EN

Revision Date: May / 2021



Printing date: May 18, 2021

6. DECLARED PERFORMANCE:

Essential characteristics	Performance	Harmonised technical specifications
Adhesion to brick and block /Fracture mode	≥ 0.2 N/mm²/ B	EN 998-2:2016
Capillary water absorption	Class W _c 1	
Water vapour permeability	μ ≤ 20	
Reaction to fire	Class A1	
Thermal conductivity / Density (table value)	(λ 10, dry) 0.45 W/m.K (P= 50%)	
Durability	Until there is a standard test, assessment is based on provisions validated where the mortar is used	
Hazardous Substances	Please refer to the SDS*	

^{*} SDS - Safety Data Sheet

7. The performance of the product identified above is in accordance with the declared performance set. This declaration of performance is issued in accordance with regulation (EU) No. 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of manufacturer by:

Dina Frade

(Operational Management)

Maceira, 18 May 2021